

Launching soon

Compact flight type dishwasher

Optimizing performance with compact design

Characteristics and advantages

- **High productivity:** Up to 3800 dishes/h
- **Water and energy savings:** 15% less water and 17% less energy with insulation door
- **Guaranteed hygiene:** Precise thermal control of rinse water temperature
- **Built-in pressure reducer:** Stable rinse water pressure during the rinse phase
- **Easy to use:** Panel with temperature display
- **Easy to service and maintain:** Electrical control box and main components on top and front
- **Quick on-site installation:** Using preset external chemical connection terminal
- **Avoid injury risk:** Washing will stop when door is open
- **Safety first:** Designed to prevent dry heating failure at low water levels

| PNC | 521005 | 521006 | 521011 | 521012 |
|-------------------------------|---------------|--------|--------|--------|
| Model | FTS-L | FTS-R | FTS-LT | FTS-RT |
| External dimension (W*D*H mm) | 2950*876*1673 | | | |
| Loading direction | L>R | R>L | L>R | R>L |
| Electric supply | 380V/50Hz/3N | | | |
| Installed power (kW) | 45 | 45 | 57 | 57 |
| Max productivity (dishes/h) | 3800 | | | |
| Clearance (mm) | 412*612 | | | |
| Wash temperature (°C) | 55-60 | 66-71 | | |
| Rinse temperature (°C) | 82-90 | | | |
| Rinse water consumption (l/h) | 350 | | | |
| Inlet water pressure (bar) | 2-5 | | | |
| Inlet water temperature (°C) | 10-60 | | | |
| Inlet pipe size (inch) | G 3/4" | | | |
| Drain pipe size (inch/mm) | 2" or 50mm | | | |

